

WHAT IS CLAIMED IS:

1. A myotherapy massage device for the treatment of lower back myofosical pains, the device comprising:

two laterally spaced massage heads, with each massage head having vibration means;

5 a means for positioning the massage heads vertically relative to one another; and

a means for positioning the massage heads laterally relative to one another.

2. The device according to Claim 1, wherein each massage head has a motor housing enclosing the vibration means, wherein the motor housing comprises

a tube having a bottom end, and a top end;

5 a bottom cap disposed on the bottom end;

a top cap disposed on the top end opposite the bottom cap; and

wherein the vibration means is disposed within the motor housing.

3. The device according to claim 2, further comprising a retention plate disposed between the top and bottom ends of the tube wherein the top cap contacts and rests upon the retention plate, thereby creating top and bottom spaces within the motor housing such that the top space adjacent the
5 top cap is smaller than the bottom space adjacent the bottom cap.

4. The device according to claim 3, wherein the vibration means comprises a motor which turns an asymmetric weight thereby producing vibration.

5. The device according to claim 4, wherein the motor is disposed in the bottom space and attached to the retention plate and the weight is permitted free movement in the top space.

6. The device according to claim 2, wherein the top cap has a convex top surface.

7. The device according to Claim 2, further comprising a means for heating the top cap.

8. The device according to Claim 7, wherein the means for heating the top cap is taken from the group consisting of heating coils, infrared radiation, resistance wires, and resistance wire tape disposed within the top cap and in contact thereto for conducting heat therethrough.

9. The device according to Claim 7, wherein the top cap is composed of a heat conducting material.

10. The device according to Claim 2, further comprising a coil compression spring disposed in the motor housing between the bottom cap and the top cap thereby cushioning the vibration means such that the vibration of the massage head is dampened with respect to the motor housing and amplified with respect to the top cap.

11. The device according to Claim 3, further comprising a coil compression spring disposed in the motor housing between the bottom cap and the retention plate thereby cushioning the vibration means such that the vibration of the massage head is dampened with respect to the motor housing.

12. The device according to Claim 2, further comprising an edge circumnavigating the tube adjacent the bottom end of the tube such that some length of tube extends therebelow.

13. The device according to Claim 1, wherein the means for positioning the massage heads laterally relative to one another comprises an apparatus having two opposing base assemblies slidably connected to each other by two guide rods, wherein each base assembly comprises two opposing
 5 bases having the means for positioning the massage heads vertically relative to one another disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod.

14. The device according to Claim 13, further comprising means for restricting the movement of the base assemblies relative to the guide rods.

15. The device according to Claim 13, wherein each guide further comprises a perpendicular threaded second opening, bisecting the first opening, for receiving a knob having a screw extension thereon which can be tightened to secure the guide rod in place.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

16. The device according to Claim 1, wherein the means for positioning each massage head vertically comprises:

a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft.

17. The device according to claim 16, wherein the crankshaft has a means for rotating the crankshaft disposed on the first end of the crankshaft.

18. The device according to claim 16, further comprising a bend in the lift arm.

19. The device according to claim 16, wherein the second end of the lift arm comprises a U-shaped extension such that the pivot axis assembly fits between two legs of the U-shaped extension.

20. The device according to Claim 19, wherein the two legs of the U-shaped extension extend past the pivot axis.

21. The device according to Claim 1, further comprising a controller for modulating the vibration frequency.

22. The device according to Claim 1, wherein the vibration means operates at a vibration frequency

- (i) greater than about 90 Hz, and
- (ii) less than about 110 Hz.

23. The device according to Claim 1, wherein the vibration means operates at a vibration frequency of about 100±5 Hz.

24. The device according to Claim 1, wherein the means for positioning the massage heads laterally comprises a base assembly having two opposing bases slidably engaged in a track on a platform.

25. The device according to Claim 1, wherein the means for positioning massage heads vertically comprises a base assembly having two opposing bases having massage heads slidably engaged in each base such that the massage heads can individually be positioned vertically.

26. A myotherapy massage device for the treatment of lower back myofosical pains, the device comprising:

two laterally spaced massage heads,

wherein each massage head has a motor housing enclosing a

5 vibration means,

the motor housing has a tube having bottom and top ends,

a bottom cap disposed on the bottom end of the motor housing,

and

a top cap disposed on the top end of the motor housing opposite

10 the bottom cap;

a means for positioning the massage heads vertically relative to one another; and

a means for positioning the massage heads laterally relative to one another.

27. The device according to Claim 26, wherein the means for positioning the massage heads laterally comprises an apparatus having two opposing base assemblies slidably connected to one another by two guide rods, wherein each base assembly comprises two opposing bases having the means
5 for positioning the massage heads vertically disposed between the bases, and a guide disposed on each base having a first opening therethrough for slidably receiving a guide rod.

28. The device according to Claim 27, wherein the means for positioning each massage head vertically comprises:

a base assembly composed of two opposing bases and a lift arm disposed between the two opposing bases;

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift arm;

a linker, having first and second ends, with the first end of the linker pivotably disposed on the lift axis and the second end of the linker pivotably disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a passage therethrough for receiving a crankshaft therethrough and a second threaded opening forming a means for receiving the pivot axis of the second end of the lift arm;

the crankshaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing bases and having a threaded opening for receiving a first end of the crank shaft therethrough; and

a second spacer block attached to and disposed between the two opposing bases and having a threaded opening therein for receiving a second end of the crankshaft.

29. The device according to Claim 28, wherein the means for attaching the massage head to the first end of the lift arm comprises an opening therethrough for receiving the motor housing of the massage head.

30. The device according to claim 28, wherein the crankshaft has a handle for rotating the shaft disposed on the first end of the shaft.

31. The device according to claim 29, further comprising a bend in the lift arm at the lift axis.

32. A massage device comprising:

a massage head having a motor housing enclosing a vibration means,
the motor housing has a tube having bottom and top ends,
a bottom cap disposed on the bottom end of the motor housing,

5 and

a top cap disposed on the top end of the motor housing opposite
the bottom cap; and

a means for positioning each massage head vertically comprising a base
assembly composed of two opposing bases and a lift arm disposed between the
two opposing bases;

10

the lift arm has a length with a first and second end,

a means for attaching a massage head at the first end

a pivot axis at the second end thereof, and

a lift axis disposed between the first and second ends of the lift

15

arm;

a linker, having first and second ends, with the first end of the linker
pivotably disposed on the lift axis and the second end of the linker pivotably
disposed between the two opposing bases;

a pivot axis assembly having a first threaded opening therein forming a
passage therethrough for receiving a crankshaft therethrough and a second
threaded opening forming a means for receiving the pivot axis of the second
end of the lift arm;

20

the crank shaft having a length, a first end, and a second end;

a first spacer block attached to and disposed between the two opposing

25

bases and having a threaded opening for receiving a first end of the crank shaft
therethrough; and

a second spacer block attached to and disposed between the two
opposing bases and having a threaded opening therein for receiving a second
end of the crankshaft.

33. The device according to Claim 32, wherein the means for
attaching the massage head to the first end of the lift arm comprises an opening
therethrough for receiving the motor housing of the massage head.

34. The device according to claim 32, wherein the crankshaft has a handle for rotating the shaft disposed on the first end of the shaft.

35. The device according to claim 32, further comprising a bend in the lift arm at the lift axis.

36. A method for treating myofascial pain in the lower back of a user by relieving tension in the lower back muscles, said method comprising:

providing a massage device having two laterally spaced massage heads, each massage head having vibration means, a means for positioning the massage heads vertically relative to one another, and a means for positioning the massage heads laterally relative to one another;

placing the massage device on a sturdy flat surface;

placing the back on the device such that each massage head comes into contact with the opposite sides of the lower back thereby applying pressure to the areas of contact

adjusting each massage head's relative position; and

applying vibration to the desired locations of the lower back.

37. The method of claim 36, wherein the areas of contact are the outer sides of the muscles that run along both sides of the spine.

38. The method of claim 36, wherein the vibration is applied for about one to two minutes.

39. The method of claim 36, wherein the massage head has a means for heating the areas of contact.

40. The method of claim 39, wherein the vibration and heat are applied for about one to two minutes.